

SUPREM 5000

El sistema se compone de dos subgraves G-15/1 y G-15/2 y un satélite (TOP 12) por stack. El G15/2 incorpora la etapa de potencia para el satélite TOP -12.

The system is composed by: two subs and one satellite per stack: G15/1 , G15/2 (this one with the amplifier for the satellite) and the TOP 12.



TOP-12

G-15/1

G-15/2

componentes / components	12" + 1,75" DRIVER	15"	15"
diseño / design	Reflex	Bocina plegada + reflex Folded horn + reflex	Bocina plegada + reflex Folded horn + reflex
potencia (rms/prog/pico) / power (rms/prog/peak)	500 W	-	-
modulos de potencia / power modules	-	600 W	600 W + 450 W
rango de frecuencias / frequency range	130Hz / 19KHz	39,8 Hz / 130 Hz	39,8 Hz / 130 Hz
respuesta de frecuencia / frequency response	135Hz - 18,5KHz	-	-
cobertura / coverage	60 x 40	-	-
SPL (1W/1m) / SPL (1W/1m)	100dB	101,5dB	101,5dB
SPL pico máximo / SPL maximum peak	132dB	134dB	134dB
impedancia / impedance	8 Ω	-	-
conectores / connectors	SPEAKON 4 PIN	XLR3 + POWERCON	XLR3 + POWERCON
composición del recinto / enclosure material	Contrachapado 12mm 12mm PLYWOOD	Contrachapado 15mm 15mm PLYWOOD	Contrachapado 15mm 15mm PLYWOOD
acabado / finish	POLYMPACT	POLYMPACT	POLYMPACT
rejilla / grid	Hierro acabado Epoxy epoxy finished iron	Hierro acabado Epoxy epoxy finished iron	Hierro acabado Epoxy epoxy finished iron
espuma / foam	Acusticamente transparente Acoustically transparent	Acusticamente transparente Acoustically transparent	Acusticamente transparente Acoustically transparent
dimensiones (mm) / dimensions (mm)	523 x 584 x 535	531 x 641 x 643	531 x 641 x 643
peso (Kg) / weight (Kg)	37,9	55,4	59